

MANUAL HONEYCOMB SKYLIGHT



Structure Drawing



- 1. Top track
- 2. Connector
- 3. Retractable rod
- 4. Fabric

- 5. Front Driving Beam
- 6. Side Track

Components List

Top track /Bottom rail		Size: 33×30mm Material: Aluminum Thickness: 1.0mm Color: White/Grey/Beige/Matt black Color could be customized (MOQ:500pcs)
Fabric		Size:25/45mm Material: Polyester 100% Color: White There are more colors available, please contact customer service for all electronic and physical color cards.
Top track		Size: 32×52×31mm Material: POM Color: White/Grey/Beige/Matt black Match with top track
Front driving beam		Size: 41x21mm Material: Aluminum Thickness: 1.0mm Color: White/Grey/Beige/Matt black Match with top track
Side track		Size: 33x30mm Material: Aluminum Thickness: 1.0mm Color: White/Grey/Beige/Matt black Match with top track
Retractable rod		Size:Ø28mm Material:Aluminum Color:Aolly Tlelscopic distance:1060~2020mm
Expansion screws	#	Size:M6x50mm

Measuring method

Motorized honeycomb skylight Installation Measuring Method:

Width: Inside edge of roof size from top, middle and bottom distance. (Orange line show as below pic) Length: Measure the distance from left to right pf inside of roof (Grey line show as below pic) Use the minimum size for awning's readymade size among the noted measuring width and length.

Inside depth ≥50mm.



Package types

Inner packing



Outer Packing



5 layers thicken carton + angle protection for 4 edges

Packing Real Site













Tianjin Hunters Technology Co., Ltd

- No.6 building, Changqingteng Art & Industrial Park, No.10 Caizhi Road, Jingwu town, Xiqing District, Tianjin, China. Post code: 300392
- **(** +86 22 23982209
- +86 15922294041
- ▼ lauraoo1@aliyun.com